




Kennesaw State University Soccer Stadium, Kennesaw, GA, USA

Completed in record time, over 200 squares of 4" Rib panels were used in a custom black to match the university's school color in a design to reflect the surrounding mountains.




4" RIB EXPOSED FASTENER ROOFING & SIDING PANEL


Fabral® 4" Rib is a classically designed exposed fastener panel with 4" Rib spacing. With exceptional durability and unlimited color options, 4" Rib is a preferred choice for function and creativity. The unique construction of 4" Rib allows panels to follow every curve of your design. And it's suitable for use on both wall and roof applications (in siding only, can be applied in vertical and horizontal orientation). With 4" Rib your vision is limitless.



Panels shown are the standard options with nominal dimensions as shown. Panel material (ie steel or aluminum) and paint type will limit available option. Contact Fabral for more information.



Roof & Wall Application



Wall Only Application

Other versions available. See Panel Options document or contact Fabral for more information.

4" RIB

BRIEF PRODUCT SPECIFICATION

MANUFACTURER DESCRIPTION

- Fabral®, 308 Alabama Blvd, Jackson, GA 30233
- **Telephone:** 800.884.4484
- **Email:** sales@fabral.com
- **Website:** Fabral.com

PRODUCT DESCRIPTION

Acceptable Product: Fabral® 4" Rib

Class 4 Impact: UL2218

Class A Fire: UL790

Wind Uplift & Fastener Spacing calculations are available upon request

GRAVITY LOAD TABLE (PSF)

Substrate	Span	6'-0"	7'-0"	8'-0"	9'-0"	10'-0"	11'-0"	12'-0"
26 ga. Steel	3	58	43	33	26	-	-	-
24 ga. Steel	3	58	42	32	26	-	-	-
22 ga. Steel	3	78	57	44	35	28	23	-
20 ga. Steel	3	96	71	54	43	35	29	24
18 ga. Steel	3	126	93	71	56	45	38	32
.032" alum.	3	53	39	30	23	-	-	-
.040" alum.	3	73	53	41	32	26	22	-
.050" alum.	3	97	71	55	43	35	29	24

Note: Allowable loads based on AISI and Aluminum Association Specifications. Allowable loads are based on stress only.

DESIGN INFORMATION

- **Perforation available upon request**
- **Roof Slope:** Minimum required - 2 1/2:12
- **Panel Length:** Maximum - 45' Minimum - 6'
- **Panel Width Options:** 48", 32"
- **Panel Variation 8" Rib is Available**

PRODUCT INSTALLATION

Install panels plumb, level and straight so it is watertight and without waves or other distortions, allowing for thermal movement considerations. Apply sealant tape or caulking as necessary at flashing and panel joints to prevent water penetration.

PRODUCT MAINTENANCE AND WARRANTY

Fabral® provides a 30 year paint-finish warranty for cracking, chipping, peeling, fading and chalking – providing confidence in a long-lasting application.

To ensure the durability of your 4" Rib panels, use proper care. Remove filings, grease, stains, marks or excess sealants from roof panels system to prevent staining. Store panels and flashings in a safe, dry environment.

RECENT PROJECTS

Segment	Project Name	Location	Quantity	Architect/Distributor
Education	Kennesaw State University Soccer Stadium	Kennesaw, GA	200 sq	Gregory T Sweeny, Rossetti
Industrial	C.E. Storage Building - Air National Guard	Lincoln, NE	135 sq	Caspers Construction
Religious	Mt Bethel United Methodist Church	Marietta, GA	392 sq	Orion Associates, Inc
Office Building	Tumwater Office Building	Tumwater, WA	160 sq	Northshore Sheet Metal