

# DOOR TRACK SYSTEMS

## HARDWARE AND ACCESSORIES



### AVAILABLE DOOR SIZES

Standard (in stock):

- 8W X 8H
- 8W X 10H
- 8W X 12H
- 8W X 14H
- 10W X 10H
- 10W X 12H
- 10W X 14H
- 10W X 16H
- 12W X 10H
- 12W X 12H
- 12W X 14H
- 12W X 16H
- 14W X 10H
- 14W X 12H
- 14W X 14H
- 14W X 16H
- 16W X 10H
- 16W X 12H
- 16W X 14H
- 16W X 16H

Special order:

- 6W X 8H
- 6W X 10H
- 6W X 12H
- 18W X 10H
- 18W X 12H
- 18W X 14H
- 18W X 16H



### #3 Slotted Round Keyhold Track

For smooth, easy gliding operation. 14 gauge galvanized construction in self-cleaning design.




### 3-1PC Bracket

Use with #3 slotted round track. Rivets fit through keyway slots in each track section, allowing track, bracket and cover to be joined.



### 600 Jamb Latch

7" jamb latch is used on inside of jamb to secure sliding doors; can be ordered for either right or left hand applications.



### #1001 Quick Frame

Lumber fit for standard 2 x 4 or 2 x 6 and provides smooth, safe sides for door openings.



### #60 Guide Rail Bracket

Slotted hole in each leg allows both lateral and vertical adjustments. Bolts and nuts included.



### RBP-203-L Trolley

Adjustable, pivot and swing action with single strap apron. For doors 1-1/2" to 2-3/8" thickness.

(Plastic wheels with ball bearings.)




### 3-BC Bracket

This slide-on bracket face mounts for use with #3 slotted track.



### 630 Sliding Bolt Latch

Ideal for livestock/horse barns, this heavy duty 1/2" x 10" steel bolt doubles as a handle/pull, and may be used at left or right.



### #1002 H-Frame

Designed for use with bi-parting doors, provides concealed mating between units covering both door edges.



### #64 Rail Guide

Fabricated from 16 gauge galvanized steel and mounts with #60 brackets. Engages the bottom door guides to hold the door in place.



### RBP-303-T Trolley

Bolt-through simplicity with pivot/swing action. A 1/2" x 9" offset bolt adjusts easily. Generous vertical adjustment for various door materials.

(Plastic wheels with ball bearings.)




### 540 Door Stop

For 2" doors, made from rugged zinc-plated steel and ribbed to increase strength. Holes accept 5/16" bolts or lag screws.




### 800 Stay Roller

Fabricated from 3/16" zinc plated steel, and adjusts from 1" to 3-3/4". Non-marking plastic wheel mounted on sturdy 1/2" bolt.



### #1003 Bottom Rail

Attaches to bottom of door and accepts the #64 rail guide to firmly anchor and guide door along building during operation. Order for doors 1-1/2" thick.



### #68 Door Stop

For use with #64 bottom door guide. Stops door and prevents from disengaging with guide rail.



Manufacturer of Door Track Hardware. Over 75 years of tradition in excellence.

